

ILS prides itself to build the highest quality lecterns around from thick aluminum profiles, blocks and plates, machined to a perfect fit and style. The lecterns are virtually free of maintenance for decades. In ILS products it is possible to remove a damaged part and renew it, or to make new fittings for future upgrades without affecting the rest of the installed system.

ILS Synergy QC delivers ILS quality with a smart design. Long version of the top is placed on a compact, narrow cabinet (Half Rack Cabinet). Long version of the top is divided into two working areas. On the left is a monitor 24", mounted inside the working surface. On the right is a smooth aluminum surface for handwritten notes, laptop or control panel. A holder for the micro PC is installed inside the working surface.

This lectern also provides two fixed horizontal side tables (can be upgraded to the flip or sliding tables). This makes it possible to use extra space for handwritten notes, laptop, or place a document camera on it. The built-in switcher or four sockets with the type on request will be great helpers when handling connections between the main screen of the lectern and/or laptop, or other devices. To do this, there are four buttons on the top panel of the product. There are also two USB 3.0 sockets and a holder with built-in charging cables for tablets and smartphones. The microphone socket is of the XLR shock-mount type and there is the provision for a reading light, controlled by the button. The cabinet has a keyboard drawer and two lockable compartments with shelves to house a PC and other devices. The top compartment has a drop-down cover and a power strip to feed any laptop as well as hiding place for laptop power supplies. The larger compartment has a glass door and 2 shelves.

For mobility and rock-solid stability of the lectern during the presentation, 4 side-ways rollers are embedded in the bottom plate. In addition, we will be pleased to engrave your logo on the front panel of the lectern, in case of using the system in formal events!



DIMENSIONS

Width	Top: 1030 mm Side Plate: 300mm x 370 mm Top + Side Plate: 1675 mm Cabinet: External: width: 485 mm height: 850 mm depth: 470 mm Internal: width: 305 mm height: 615 mm depth: 460 mm Tilt adjustment: 12° - 20°
Height	User side: 1010 mm Audience Side: 1140 mm
Weight	90 kg

INTEGRATION

Display & PC	Monitor: 24" Dell 2418HT IPS; 10 points capacitive touchscreen (up to 30") PC: Dell Optiplex 3070 micro Intel Core I-5 CPU; 8GB RAM; 256GB SSD;
Accessories	Switcher: ILS503 switcher or 4 x sockets (type on request) Audio: 1 x Microphone: AKG CGN 99 Light: 1 x Light: LITTLITE LED XLR-4 lamp
Features	ILS holder for micro PC installation inside working surface Extra space on the right from the display for laptop or notes <27" monitor Ultra Wide Phone/Tablet holder Half Rack Cabinet 5 x Buttons (4 x Signal switch; 1 x Light;) 2 x Side tables 1 x Keyboard drawer 2 x Lockable compartments (1 x Metal door; 1 x Glass door;) 4 x Lockable smart castors or sideway rollers

CONNECTIVITY

Top	1 x 3-Pin XLR Shock Mount for microphone 1 x BNC Light socket (12V) 2 x USB 3.0 Sockets 3 x Charging cables (USB type-C; Lightning; micro USB;)
Bottom	1 x HDMI; 1 x PC LAN; 1 x XLR microphone; 1 x 3.5mm Audio; 1 x AC Power; 1 x HDbaseT; 1 x Switcher Control Cable;

